

Product data sheet

Specifications



Limit switch body, Limit switches XC Standard, ZCT, compact, 1NC+1 NO, slow break, Pg11

ZCT25G11

Main

| | |
|-------------------------------|---|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard compact |
| Product or component type | Limit switch body |
| Device short name | ZCT |
| Design | Compact |
| Body type | Fixed |
| Associated head | ZCE63 ZCE01 ZCE02 ZCE13 ZCE66 ZCE08 ZCE21 ZCE28 ZCE62 ZCEH0 ZCE06 ZCE10 ZCE67 ZCE29 ZCE05 ZCEH2 ZCE07 ZCE24 ZCE27 ZCE65 ZCE11 ZCE64 ZCE14 |
| Body material | Plastic |
| Number of poles | 2 |
| Contacts type and composition | 1 NC + 1 NO |
| Contact operation | Slow-break, break before make |
| Complementary | |
| Electrical connection | Screw-clamp terminals, clamping capacity: 1 x 0.5...2 x 2.5 mm ² |
| Cable entry | 2 entries tapped for Pg 11 cable gland, cable outer diameter: 4...8 mm |
| Contacts insulation form | Zb |
| Contacts material | Silver plated contacts |
| Positive opening | With |
| Minimum actuation speed | 6 m/s |

| | |
|---|---|
| Contact code designation | B300, AC-15 (Ue = 240 V), Ie = 1.5 A conforming to EN/IEC 60947-5-1 appendix A R300, DC-13 (Ue = 250 V), Ie = 0.1 A conforming to EN/IEC 60947-5-1 appendix A |
| [Ui] rated insulation voltage | 300 V conforming to UL 508 500 V (pollution degree 3) conforming to IEC 60947-1 300 V conforming to CSA C22.2 No 14 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60664 6 kV conforming to IEC 60947-1 |
| Short-circuit protection | 10 A cartridge fuse, type gG |
| Electrical durability | 5000000 cycles, DC-13 120 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 13 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width | 58 mm |
| Height | 51 mm |
| Depth | 30 mm |
| Net weight | 0.13 kg |

Environment

| | |
|--|-------------|
| Product compatibility | XCKT |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |

Packing Units

| | |
|-------------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.5 cm |
| Package 1 Width | 5.5 cm |
| Package 1 Length | 6.2 cm |
| Package 1 Weight | 80.0 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 72 |
| Package 2 Height | 15.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 6.307 kg |

Offer Sustainability

| | |
|-----------------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known |

Contractual warranty

Warranty 18 months

Recommended replacement(s)