

# Pluggable Terminal Blocks

## 5.08 mm Pitch



### FEATURES:

- Polarised Mouldings
- Withstand Voltage - AC1500V/1min
- Pin/Terminal - Tin plated brass
- Screw/Torque - M2.5 Steel, Nickel Plated 0.4Nm
- Recommended PCB hole size  $\phi 1.7$  mm
- Guided pin alignment



### SPECIFICATION:

Gender of contacts	Female
Rated current to EN	15 A
Pitch	5.08 mm
Component type	Wire socket 90°
Termination type	Screw Connection
Connection direction	vertical
Rated voltage to EN	300 V
Combustibility class	UL 94 V-0
Colour	green
Temperature range	-40...+105 °C
Cross-section max.	2.0 mm <sup>2</sup>
Cross-section min.	0.33 mm <sup>2</sup>
Connection cross-section	0.33-2 mm <sup>2</sup> (22-14AWG)

### PRODUCT RANGE:

Art. Nr.	Poles	A	Length
RND 205-00177	2	10.2 mm	10.2 mm
RND 205-00178	3	15.2 mm	15.2 mm
RND 205-00179	4	20.3 mm	20.3 mm
RND 205-00180	5	25.4 mm	25.4 mm
RND 205-00181	6	30.5 mm	30.5 mm
RND 205-00183	8	40.6 mm	40.6 mm
RND 205-00184	9	45.7 mm	45.7 mm

