

**Illuminated pushbutton actuator, RMQ-Titan, Flush, momentary, White,
Blank, Bezel: titanium**



Part no. M22-DL-W
216922
EL Number 4355342
(Norway)

| | |
|-----------------------------------|--|
| Product name | Eaton Moeller® series M22 Illuminated pushbutton actuator |
| Part no. | M22-DL-W |
| EAN | 4015082169220 |
| Product Length/Depth | 30 millimetre |
| Product height | 30 millimetre |
| Product width | 30 millimetre |
| Product weight | 0.01 kilogram |
| Compliances | CE Marked |
| Certifications | UL 508 CSA Std. C22.2 No. 14-05 CSA Std. C22.2 No. 94-91 IEC 60947-5 EN 60947-5 VDE UL Category Control No.: NKCR CSA File No.: 012528 CSA Class No.: 3211-03 CSA CSA-C22.2 No. 14-05 IEC/EN 60947-5 IEC/EN 60947 CE VDE 0660 UL File No.: E29184 CSA-C22.2 No. 94-91 UL DNV GL LR |
| Product Tradename | M22 |
| Product Type | Illuminated pushbutton actuator |
| Product Sub Type | None |
| Globally Marketable | Yes |
| Bezel color | Chrome |
| Bezel material | Plastic |
| Color | White |
| Design | Flush Classical |
| Fitted with: | Front ring |
| Inscription | Blank |
| Degree of protection | IP66 IP69K NEMA 12 NEMA 13 NEMA 4X NEMA 3R IP67 |
| Degree of protection (front side) | IP67/IP69K NEMA 4X |
| Lifespan, mechanical | 5,000,000 Operations |
| Opening diameter | 22.5 mm |
| Operating frequency | 3600 Operations/h |
| Product category | RMQ-Titan |
| Size | Front dimensions: 22 x 22 mm |
| Suitable for | Illumination |
| Type | Illuminated pushbutton actuator |

| | | |
|--|--|--|
| Mounting position | | As required |
| Shock resistance | | 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27 |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 70 °C |
| Climatic proofing | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Connection to SmartWire-DT | | With SWD-RMQ connections Yes |
| Actuating force | | 5 N |
| Actuator color | | White |
| Actuator function | | Momentary Spring-return |
| Force for positive opening - min | | 0 N |
| Equipment heat dissipation, current-dependent Pvid | | 0 W |
| Heat dissipation capacity Pdis | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 0 W |
| Rated operational current for specified heat dissipation (In) | | 0 A |
| Static heat dissipation, non-current-dependent Pvs | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Please enquire |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | Not applicable. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 8.0

| | | |
|--|----|-------|
| Low-voltage industrial components (EG000017) / Front element for push button (EC000221) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss10.0.1-27-37-12-10 [AKF028014]) | | |
| Colour button | | White |
| Number of command positions | | 1 |
| Construction type lens | | Round |
| Hole diameter | mm | 22.5 |

| | | |
|---|----|------------|
| Width opening | mm | 0 |
| Height opening | mm | 0 |
| Type of button | | Flat |
| Suitable for illumination | | Yes |
| With protective cover | | No |
| Labelled | | No |
| Switching function latching | | No |
| Spring-return | | Yes |
| With front ring | | Yes |
| Material front ring | | Plastic |
| Colour front ring | | Chrome |
| Degree of protection (IP), front side | | IP67/IP69K |
| Degree of protection (NEMA), front side | | 4X |